

CLAIMS

What is claimed is:

1. A method of content level filtering and distribution of digital content in a content distribution system comprising:
 - obtaining the digital content and a mask for obfuscating a selected portion of the digital content;
 - determining if a receiver of the digital content is trusted;
 - sending the digital content to the receiver for subsequent rendering when the receiver is trusted; and
 - applying the mask to the digital content to generate content after mask applied data and sending the content after mask applied data to the receiver for subsequent rendering of the content after mask applied data when the receiver is not trusted.
2. The method of claim 1, wherein the digital content comprises video data and the mask comprises a replacement two dimensional region for a selected portion of one or more frames of video data.
3. The method of claim 1, wherein the digital content comprises audio data and the mask comprises a replacement audio clip for a selected portion of the digital content.
4. The method of claim 1, wherein the digital content comprises three dimensional volume data and the mask comprises a replacement three dimensional region for a selected portion of the digital content.
5. The method of claim 1, wherein application of the mask results in replacement of a selected portion of the digital content with a replacement creative component.

4
1 6. A method of content level filtering and distribution of digital content in a
2 content distribution system comprising:

3 obtaining the digital content and a mask for obfuscating a selected portion
4 of the digital content;

5 determining if a channel for distributing the content is trusted;

6 when the channel is not trusted, performing the following:

7 applying the mask to the digital content to generate content after
8 mask applied data and masked content;

9 encrypting the masked content;

10 determining if a receiver of the digital content is trusted;

11 sending the content after mask applied data and the encrypted
12 masked content to a receiver, decrypting the masked content, and
13 reversing masking to reproduce original content for subsequent rendering
14 when the receiver is trusted; and

15 sending the content after mask applied data to the receiver for
16 subsequent rendering of the content after mask applied data when the
17 receiver is not trusted.

18
1 7. The method of claim 6, further comprising:

2 when the channel is trusted, performing the following:

3 determining if a receiver of the digital content is trusted;

4 sending the digital content to the receiver for subsequent rendering
5 when the receiver is trusted; and

6 applying the mask to the digital content to generate content after
7 mask applied data and sending the content after mask applied data to the
8 receiver for subsequent rendering of the content after mask applied data
9 when the receiver is not trusted.

1 8. The method of claim 6, wherein the digital content comprises video
2 data and the mask comprises a replacement two dimensional region for a
3 selected portion of one or more frames of video data.

1 9. The method of claim 6, wherein the digital content comprises audio
2 data and the mask comprises a replacement audio clip for a selected portion of
3 the digital content.

1 10. The method of claim 6, wherein the digital content comprises three
2 dimensional volume data and the mask comprises a replacement three
3 dimensional region for a selected portion of the digital content.

1 11. The method of claim 6, wherein application of the mask results in
2 replacement of a selected portion of the digital content with a replacement
3 creative component.

1 12. An article comprising: a storage medium having a plurality of machine
2 readable instructions, wherein when the instructions are executed by a
3 processor, the instructions provide content level filtering and distribution of digital
4 content in a content distribution system by:

5 obtaining the digital content and a mask for obfuscating a selected portion
6 of the digital content;

7 determining if a receiver of the digital content is trusted;

8 sending the digital content to the receiver for subsequent rendering when
9 the receiver is trusted; and

10 applying the mask to the digital content to generate content after mask
11 applied data and sending the content after mask applied data to the receiver for
12 subsequent rendering of the content after mask applied data when the receiver
13 is not trusted.

1 13. The article of claim 12, wherein the digital content comprises video
2 data and the mask comprises a replacement two dimensional region for a
3 selected portion of one or more frames of video data.

1 14. The article of claim 12, wherein the digital content comprises audio
2 data and the mask comprises a replacement audio clip for a selected portion of
3 the digital content.

1 15. The article of claim 12, wherein the digital content comprises three
2 dimensional volume data and the mask comprises a replacement three
3 dimensional region for a selected portion of the digital content.

1 16. The article of claim 12, wherein application of the mask results in
2 replacement of a selected portion of the digital content with a replacement
3 creative component.

1 17. An article comprising: a storage medium having a plurality of machine
2 readable instructions, wherein when the instructions are executed by a
3 processor, the instructions provide content level filtering and distribution of digital
4 content in a content distribution system by:

5 obtaining the digital content and a mask for obfuscating a selected portion
6 of the digital content;

7 determining if a channel for distributing the content is trusted;

8 when the channel is not trusted, performing the following:

9 applying the mask to the digital content to generate content after
10 mask applied data and masked content;

11 encrypting the masked content;

12 determining if a receiver of the digital content is trusted;

13 sending the content after mask applied data and the encrypted
14 masked content to a receiver, decrypting the masked content, and

009720" T250560

15 reversing masking to reproduce original content for subsequent rendering
16 when the receiver is trusted; and
17 sending the content after mask applied data to the receiver for
18 subsequent rendering of the content after mask applied data when the
19 receiver is not trusted.

20

1 18. The article of claim 17, further comprising instructions for:
2 when the channel is trusted, performing the following:
3 determining if a receiver of the digital content is trusted;
4 sending the digital content to the receiver for subsequent rendering
5 when the receiver is trusted; and
6 applying the mask to the digital content to generate content after
7 mask applied data and sending the content after mask applied data to the
8 receiver for subsequent rendering of the content after mask applied data
9 when the receiver is not trusted.

10

1 19. The article of claim 17, wherein the digital content comprises video
2 data and the mask comprises a replacement two dimensional region for a
3 selected portion of one or more frames of video data.

1 20. The article of claim 17, wherein the digital content comprises audio
2 data and the mask comprises a replacement audio clip for a selected portion of
3 the digital content.

1 21. The article of claim 17, wherein the digital content comprises three
2 dimensional volume data and the mask comprises a replacement three
3 dimensional region for a selected portion of the digital content.

1 22. The article of claim 17, wherein application of the mask results in
2 replacement of a selected portion of the digital content with a replacement
3 creative component.

4

1

2

3

4

5

6

1

2

3

4

5

1

2

3

1

2

3

1

2

3

1

2

3

4

1

2

3

4

5

23. A system providing content level filtering and distribution of digital content comprising:

a content censor to identify regions of content to obfuscate; and

a mask generator to accept the content and regions and produce a mask to apply to the content to obfuscate the identified regions.

24. The system of claim 23, wherein the mask generator links the content with the regions, generates a mask, applies the mask to the content to produce content after mask applied data and masked content, and encrypts the masked content.

25. The system of claim 23, further comprising a distributor to transmit the content and the mask to a receiver.

26. The system of claim 23, further comprising a distributor to transmit content after mask applied data to a receiver.

27. The system of claim 23, further comprising a distributor to transmit content after mask applied data and encrypted masked content to a receiver.

28. The system of claim 25, wherein the receiver comprises a masker to apply the mask to the content to produce content after mask applied data for rendering by the receiver.

29. The system of claim 27, wherein the receiver comprises a decryptor to decrypt the encrypted masked content and a de-masker to reverse masking of the content after mask applied data to reproduce original content for rendering by the receiver.

1 30. The system of claim 23, further comprising a content creator to create
2 the digital content.

1 31. The system of claim 23, wherein the content censor comprises a
2 region identification tool to identify a region of the digital content to obfuscate.

1 32. A method of distributing digital content in a hierarchical content
2 distribution system comprising:

3 determining security of a transmission channel;

4 determining a mode of content distribution;

5 when the mode is a first mode performing:

6 obtaining the digital content and a mask to apply to the digital
7 content to obfuscate selected portions of the digital content when the
8 transmission channel is trusted; and

9 obtaining content after mask applied data when the transmission
10 channel is not trusted;

11 when the mode is not a first mode, obtaining content after mask applied
12 data and encrypted masked content; and

13 sending obtained data to other entities in the hierarchical content
14 distribution system.

1 33. The method of claim 32, further comprising sending the obtained data
2 to at least one receiver.

009T20" T250560